

# Mini Baviera

## Mini Baviera / I01.MLT.21160



\* Code example

I01.MLT.21160 . 24 . 827 . SP . 01

- 1- Product code
- 2- Power
- 3- CRI
- 4- Reflector angle
- 5- Colour

Power	CRI	Order Code	Kelvin	Lumen T <sub>c</sub> =50°
24W	CRI>80	I01.MLT.21160 . (...) . (...) . (...) . (...)	2700K	2706
			3000K	2773
			3500K	2870
			4000K	2971
			5000K	3179
	CRI>90	I01.MLT.21160 . (...) . (...) . (...) . (...)	2700K	2442
			3000K	2503
			3500K	2590
			4000K	2680
			5000K	X
	CRI>98	I01.MLT.21160 . (...) . (...) . (...) . (...)	2700K	1876
			3000K	1944
			4000K	2080
Meat COB		I01.MLT.21160 . (...) . (...) . (...) . (...)	1800K	X
Food COB		I01.MLT.21160 . (...) . (...) . (...) . (...)	2400K	X
FISH COB		I01.MLT.21160 . (...) . (...) . (...) . (...)	6600K	X

2	Watt - Driving Current	3	CRI / Kelvin	4	Reflector Angle /	5	Product Color /	
24	24W - 600mA	827	CRI>80 - 2700K	9827	CRI>98 - 2700K	SP	24° - Spot	01 white
20	20W - 500mA	830	CRI>80 - 3000K	9830	CRI>98 - 3000K	ME	36° - Medium	02 ral 9010
15	15W - 350mA	835	CRI>80 - 3500K	9840	CRI>98 - 4000K			03 black
10	10W - 250mA	840	CRI>80 - 4000K					04 gray
		850	CRI>80 - 5000K					05 dark gray
		927	CRI>90 - 2700K					06 special color
		930	CRI>90 - 3000K					
		935	CRI>90 - 3500K					
		940	CRI>90 - 4000K					



In DALI and Wireless DIM versions, Mini Baviera uses dali and wireless dim in-track adaptors.

