

Neptun Midi Surface

Neptun Midi Surface / I02.PSM.15079




* Code example


I02.PSM.15079 . 15 . 827 . WF . 01

- 1- Product code
- 2- Power
- 3- CRI
- 4- Reflector angle
- 5- Colour

Power	CRI	Order Code	Kelvin	Lumen T _C =50°
15W	CRI>80	I02.PSM.15079 . (...) . (...) . (...) . (...)	2700K	1202
			3000K	1239
			3500K	1264
			4000K	1290
			5000K	1329
	CRI>90	I02.PSM.15079 . (...) . (...) . (...) . (...)	2700K	1118
			3000K	1152
			3500K	1176
			4000K	1200
			5000K	X
	CRI>98	I02.PSM.15079 . (...) . (...) . (...) . (...)	2700K	X
			3000K	X
			4000K	X
Meat COB		I02.PSM.15079 . (...) . (...) . (...) . (...)	1800K	X
Food COB		I02.PSM.15079 . (...) . (...) . (...) . (...)	2400K	X
FISH COB		I02.PSM.15079 . (...) . (...) . (...) . (...)	6600K	X


2	Watt - Driving Current	3	CRI / Kelvin	4	Reflector Angle /	5	Product Color /
15	15W - 350mA	827	CRI>80 - 2700K	 WF 110° - Wide Flood	01	white	
11	11W - 250mA	830	CRI>80 - 3000K			02	ral 9010
		835	CRI>80 - 3500K			03	black
		840	CRI>80 - 4000K			04	gray
		850	CRI>80 - 5000K			05	dark gray
		927	CRI>90 - 2700K			06	special color
		930	CRI>90 - 3000K				
		935	CRI>90 - 3500K				
						940	CRI>90 - 4000K

Neptun Midi AC Surface / I02.PSM.15079 . () . () . () . () . AC



Lower height versions available with combination of AC PCB board technology that creates advantage for areas with low ceiling height.

Neptun Midi In-Track Surface / I02.PSM.15079 . () . () . () . () . IN



Neptun Midi Surface can be mounted on 3-Phase Track via in-track adaptor.