

Pipa Midi Pendant

Pipa Midi Pendant / I01.MLP.17070



* Code example


I01.MLP.17070 . 15 . 827 . SP . 01

- 1- Product code
- 2- Power
- 3- CRI
- 4- Reflector angle
- 5- Colour


Power	CRI	Order Code	Kelvin	Lumen T _c =50°
15W	CRI>80	I01.MLP.17070 . (...) . (...) . (...) . (...)	2700K	1250
			3000K	1281
			3500K	1326
			4000K	1372
			5000K	1468
	CRI>90	I01.MLP.17070 . (...) . (...) . (...) . (...)	2700K	1125
			3000K	1152
			3500K	1193
			4000K	1234
			5000K	X
	CRI>98	I01.MLP.17070 . (...) . (...) . (...) . (...)	2700K	863
			3000K	895
			4000K	939
Meat COB		I01.MLP.17070 . (...) . (...) . (...) . (...)	1800K	X
Food COB		I01.MLP.17070 . (...) . (...) . (...) . (...)	2400K	X
FISH COB		I01.MLP.17070 . (...) . (...) . (...) . (...)	6600K	X

2	Watt - Driving Current	3	CRI / Kelvin	4	Reflector Angle /	5	Product Color /	
15	15W - 350mA	827	CRI>80 - 2700K	9827	CRI>98 - 2700K	SP	20° - Spot	01 white
10	10W - 250mA	830	CRI>80 - 3000K	9830	CRI>98 - 3000K	FL	40° - Flood	02 ral 9010
7	7W - 180mA	835	CRI>80 - 3500K	9840	CRI>98 - 4000K	WF	60° - Wide Flood	03 black
4	4W - 100mA	840	CRI>80 - 4000K					04 gray
		850	CRI>80 - 5000K					05 dark gray
		927	CRI>90 - 2700K					06 special color
		930	CRI>90 - 3000K					
		935	CRI>90 - 3500K					
		940	CRI>90 - 4000K					


Profile Height for ON-OFF version /




Profile Height for Phase-Cut DIM /




Profile Height for 1-10V, DALI and Warm DIM /



Profile Height for Wireless DIM /



Profile Height for Emergency version /



Steel suspension cord with up to 5mt length option.



Ceiling rose cover with integrated cable cord grip integrated.