

Pipa Mini

Pipa Mini / I01.MLS.17080



* Code example

I01.MLS.17080 . 7 . 827 . SP . 01

- 1- Product code
- 2- Power
- 3- CRI
- 4- Reflector angle
- 5- Colour

Power	CRI	Order Code	Kelvin	Lumen T _c =50°
7W	CRI>80	I01.MLS.17080 . (..) . (...) . (..) . (..)	2700K	720
			3000K	737
			3500K	763
			4000K	790
			5000K	845
	CRI>90	I01.MLS.17080 . (..) . (...) . (..) . (..)	2700K	648
			3000K	663
			3500K	686
			4000K	710
			5000K	X
	CRI>98	I01.MLS.17080 . (..) . (...) . (..) . (..)	2700K	496
			3000K	516
			4000K	540
Meat COB		I01.MLS.17080 . (..) . (...) . (..) . (..)	1800K	X
Food COB		I01.MLS.17080 . (..) . (...) . (..) . (..)	2400K	X
FISH COB		I01.MLS.17080 . (..) . (...) . (..) . (..)	6600K	X

2	Watt - Driving Current	3	CRI / Kelvin	4	Reflector Angle /	5	Product Color /	
7	7W - 180mA	827	CRI>80 - 2700K	9827	CRI>98 - 2700K	SP	20° - Spot	01 white
4	4W - 100mA	830	CRI>80 - 3000K	9830	CRI>98 - 3000K	ME	35° - Medium	02 ral 9010
		835	CRI>80 - 3500K	9840	CRI>98 - 4000K	FL	45° - Flood	03 black
		840	CRI>80 - 4000K					04 gray
		850	CRI>80 - 5000K					05 dark gray
		927	CRI>90 - 2700K					06 special color
		930	CRI>90 - 3000K					
		935	CRI>90 - 3500K					
		940	CRI>90 - 4000K					

Profile Height for ON-OFF version /




Profile Height for Phase-Cut DIM /



Profile Height for 1-10V, DALI and Warm DIM /



Profile Height for Wireless DIM /



Profile Height for Emergency version /

