


Pipa / I01.MLS.17010



Power	CRI	Order Code	Kelvin	Lumen T _c =50°
28W	CRI>80	I01.MLS.17010 . (..) . (..) . (..) . (..)	2700K	3565
			3000K	3710
			3500K	3840
			4000K	3975
			5000K	4253
	CRI>90	I01.MLS.17010 . (..) . (..) . (..) . (..)	2700K	3209
			3000K	3289
			3500K	3405
			4000K	3523
			5000K	X
	CRI>98	I01.MLS.17010 . (..) . (..) . (..) . (..)	2700K	2459
			3000K	2564
			4000K	2743
Meat COB		I01.MLS.17010 . (..) . (..) . (..) . (..)	1800K	2052
Food COB		I01.MLS.17010 . (..) . (..) . (..) . (..)	2400K	2113
FISH COB		I01.MLS.17010 . (..) . (..) . (..) . (..)	6600K	2905

* Code example


I01.MLS.17010 . 28 . 827 . SP . 01

1 2 3 4 5


- 1- Product code
- 2- Power
- 3- CRI
- 4- Reflector angle
- 5- Colour

2	Watt - Driving Current	3	CRI / Kelvin	4	Reflector Angle /	5	Product Color /	
28	28W - 700mA	827	CRI>80 - 2700K	9827	CRI>98 - 2700K	SP	20° - Spot	01 white
24	24W - 600mA	830	CRI>80 - 3000K	9830	CRI>98 - 3000K	ME	30° - Medium	02 ral 9010
20	20W - 500mA	835	CRI>80 - 3500K	9840	CRI>98 - 4000K	FL	40° - Flood	03 black
15	15W - 350mA	840	CRI>80 - 4000K	MEAT	1800K	WF	60° - Wide Flood	04 gray
		850	CRI>80 - 5000K	GOLD	2400K			05 dark gray
		927	CRI>90 - 2700K	FISH	6600K			06 special color
		930	CRI>90 - 3000K					
		935	CRI>90 - 3500K					
		940	CRI>90 - 4000K					


Profile Height for ON-OFF version /



Profile Height for Phase-Cut DIM /




Profile Height for 1-10V, DALI and Warm DIM /



Profile Height for Wireless DIM /



Profile Height for Tunable White DIM /



Profile Height for Emergency version /

