


# Trimo Micro

## Trimo Micro / I01.MLR.18005












Power	CRI	Order Code	Kelvin	Lumen T <sub>c</sub> =50°
15W	CRI>80	I01.MLR.18005 . (..) . (...) . (..) . (..)	2700K	1250
			3000K	1281
			3500K	1326
			4000K	1372
			5000K	1468
	CRI>90	I01.MLR.18005 . (..) . (...) . (..) . (..)	2700K	1125
			3000K	1152
			3500K	1193
			4000K	1234
			5000K	X
	CRI>98	I01.MLR.18005 . (..) . (...) . (..) . (..)	2700K	863
			3000K	895
			4000K	939
Meat COB		I01.MLR.18005 . (..) . (...) . (..) . (..)	1800K	X
Food COB		I01.MLR.18005 . (..) . (...) . (..) . (..)	2400K	X
FISH COB		I01.MLR.18005 . (..) . (...) . (..) . (..)	6600K	X

\* Code example

I01.MLR.18005 . 15 . 827 . SP . 01

- 1- Product code
- 2- Power
- 3- CRI
- 4- Reflector angle
- 5- Colour

2	Watt - Driving Current	3	CRI / Kelvin	4	Reflector Angle /	5	Product Color /	
15	15W - 350mA	827	CRI>80 - 2700K	9827	CRI>98 - 2700K		SP 20° - Spot	 01 white
10	10W - 250mA	830	CRI>80 - 3000K	9830	CRI>98 - 3000K		FL 40° - Flood	 02 ral 9010
7	7W - 180mA	835	CRI>80 - 3500K	9840	CRI>98 - 4000K		WF 60° - Wide Flood	 03 black
4	4W - 100mA	840	CRI>80 - 4000K					 04 gray
		850	CRI>80 - 5000K					 05 dark gray
		927	CRI>90 - 2700K					 06 special color
		930	CRI>90 - 3000K					
		935	CRI>90 - 3500K					
		940	CRI>90 - 4000K					

(..) / Complete Code



Die-Cast Aluminium heatsink with cooling pins enables very high performance cooling despite limited area enables high lumen flux from 60mm diameter of the fixture.